



GE
Lighting

96721 - GE332-MVPS-L

GE LFL UltraStart® Electronic Program / Rapid Start Ballast

- A new generation of ultra-efficient Programmed Start ballasts (> 90% efficiency).
- Anti-striation circuitry reduces striations with energy saving lamps
- Extends lamp life in frequently switched applications (> 100,000 on/off cycles)
- Multi-Voltage Technology handles voltage from 120 to 277V
- Parallel lamp operation means system maintenance is easier to manage
- Starting time visually the same as instant start

GENERAL CHARACTERISTICS

Application	3 F32T8 120V-277V Low Watts .71 BF <10% THD UltraStart
Category	Linear Fluorescent
Ballast Type	Electronic - Program / Rapid Start
Starting Method	Programmed start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Case Temperature (MAX)	70.0 °C
Ballast Factor	Low-PS (.71)
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal
Additional Info	Anti-striation control / Thermally protected / Universal voltage

PRODUCT INFORMATION

Product Code	96721
Description	GE332-MVPS-L
Standard Package	Case
Standard Package GTIN	10043168967218
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
UPC	043168967211

DIMENSIONS

Case dimensions			
Length (L)		9.5 in(241.30 mm)	
Width (W)		1.7 in(43.18 mm)	
Height (H)		1.2 in(29.97 mm)	
Mounting dimensions			
Bracket Length (BL)		NaN in(NaN mm)	
Mount Length (M)		8.9 in(225.81 mm)	
Mount Width (X or F)		1.1 in(28.70 mm)	
Mount Slots (MS)		0.3 in(7.92 mm)	
Weight		1.65 lb	
Exit Type		Side	
Remote Mounting Distance		18.0 ft	
Remote Mounting Wire Gauge		18.0 AWG	
Lead lengths	Qty	Exit	Length (± 1 in.)
Black	1	Left	25.0 (635 mm)
White	1	Left	25 in (NaN mm)
Blue	2		
Red	2	Right	33.0 (838 mm)
Red/White	2	Right	33.0 (838 mm)
Yellow	2	Right	33.0 (838 mm)
		Right	47.0 (1194 mm)

ELECTRICAL CHARACTERISTICS

Supply Current Frequency (MIN)	50.0 Hz / 60.0 Hz
Supply Current Frequency	60.0 Hz

SAFETY & PERFORMANCE

- ANSI - C62.41
- cUL Listed
- FCC - CLASS A Non-Consumer
- UL Class P
- UL Listed
- UL Type 1 Outdoor
- UL Type HL
- NEMA Premium®
- Product is compliant with material restriction requirements of RoHS

SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (°F/°C)
F32T8/WM	2	120	48	0.41 A	0.75	1.56	98	1.7	10.0	60.0 °F / NaN

F32T8/WM	2	277	48	0.18 A	0.75	1.56	92	1.7	10.0	60.0 °F / NaN
F32T8/WM	3	120	63	0.54 A	0.69	1.10	99	1.7	10.0	60.0 °F / NaN
F32T8/WM	3	277	62	0.24 A	0.69	1.11	95	1.7	10.0	60.0 °F / NaN
F32T8/25W	2	120	44		0.74	1.68	98	1.7	10.0	60.0 °F / NaN
F32T8/25W	2	277	43		0.74	1.72	98	1.7	10.0	60.0 °F / NaN
F32T8/25W	3	120	57		0.66	1.16	98	1.7	10.0	60.0 °F / NaN
F32T8/25W	3	277	56		0.66	1.18	98	1.7	10.0	60.0 °F / NaN
F32T8	2	120	52	0.45 A	0.77	1.48	98	1.7	10.0	0.0 °F / NaN
F32T8	2	277	52	0.2 A	0.77	1.48	92	1.7	10.0	0.0 °F / NaN
F32T8	3	120	69	0.61 A	0.71	1.03	99	1.7	10.0	0.0 °F / NaN
F32T8	3	277	68	0.27 A	0.71	1.04	96	1.7	10.0	0.0 °F / NaN
F28T8	2	120	45	0.38 A	0.74	1.64	98	1.7	10.0	60.0 °F / NaN
F28T8	2	277	45	0.17 A	0.74	1.64	92	1.7	10.0	60.0 °F / NaN
F28T8	3	120	58	0.49 A	0.69	1.19	99	1.7	10.0	60.0 °F / NaN
F28T8	3	277	58	0.22 A	0.69	1.19	95	1.7	10.0	60.0 °F / NaN
F25T8	3	120	54	0.46 A	0.74	1.37	99	1.7	10.0	0.0 °F / NaN
F25T8	2	120	41	0.36 A	0.82	2.00	98	1.7	10.0	0.0 °F / NaN
F25T8	2	277	0	90.0 A			82	1.7	10.0	0.0 °F / NaN
F25T8	3	277	58	0.22 A	0.66	1.14	95	1.7	10.0	0.0 °F / NaN
F17T8	2	120	29	0.25 A	0.90	3.10	98	1.7	10.0	0.0 °F / NaN
F17T8	2	277	30	0.12 A	0.90	3.00	85	1.7	10.0	0.0 °F / NaN
F17T8	3	120	38	0.32 A	0.73	1.92	99	1.7	10.0	0.0 °F / NaN
F17T8	3	277	38	0.16 A	0.73	1.92	92	1.7	10.0	0.0 °F / NaN

WARRANTY INFORMATION

GE Lighting warrants to the purchaser that each ballast will be free from defects in material or workmanship for period as defined in the attached documents from the date of manufacture when properly installed and under normal conditions of use.